```
L66 ANSWER 2 OF 3 CAPLUS COPYRIGHT 2003 ACS on STN
MΑ
     1994:36255 CAPLUS
DM
     120:36255
ED
     Entered STN: 22 Jan 1994
TT
     Binders for molds and cores for casting and their manufacture
IMT
     Wu, Zhengyong; et al.
D\Delta
     Peop. Rep. China
SO
     Faming Zhuanli Shenging Gongkai Shuomingshu, 5 pp.
     CODEN: CNXXEV
DT
     Patent
     Chinese
LA
TC
     ICM B22C001-24
     56-2 (Nonferrous Metals and Allovs)
     Section cross-reference(s): 51
FAN.CNT 1
     PATENT NO.
                       KIND DATE
                                             APPLICATION NO. DATE
                       ----
PТ
     CN 1069432
                        A
                             19930303
                                             CN 1991-107467 19910814 <--
     CN 1025659
                        В
                             19940817
PRAI CN 1991-107467
                             19910814
     The binders for molds consist of petroleum pitch 40-70, solvent 30-60,
     vegetable oil residue ≤50%; and the binders for cores consist of
     vegetable oil residue 50-90, acid or base 1-15, solvent 5-45, and
     optionally rosin ≤10% for improving strength. The binders for
     molds are formed by: melting the petroleum pitch in a reaction chamber, adding the vegetable oil residue and solvent, stirring, heating to
     100° and holding for 4 h, and cooling; and the binders for core
     sand are formed by: placing vegetable oil residue in a reaction chamber.
     adding acid or base to adjust pH to >7 and Iodine value >100, heating to
     150°, adding solvent, heating to 150° and holding for 4 h,
     and cooling. By using the binders, cast articles have improved surface
     smoothness.
     binder mold core sand casting; petroleum pitch vegetable oil binder
ST
     Molds (forms)
TT
         (binders for, petroleum pitch and vegetable oil residue in)
IT
     Pitch
         (petroleum, binders containing, for molds for casting)
TT
     Fats and Glyceridic oils
     RL: USES (Uses)
         (vegetable, residues, binders containing, petroleum pitch in, for molds for
        casting)
1.66
    ANSWER 3 OF 3 WPIDS COPYRIGHT 2003 THOMSON DERWENT on STN
AN
     1994-008167 [02]
                       WPIDS
TT
     Foundry core sand binder, for casting - is obtd. by moulding sand binder,
     heating residues of vegetable oil and acid or alkali and solvent, etc.
     providing improved surface finish of casting NoAbstract.
DC
     H08 M22 P53
TN
     WU.Z
PΑ
     (WUZZ-I) WU Z
CYC
     1
PΤ
     CN 1069432
                   A 19930303 (199402)*
C 19940817 (199536)
                                                       B22C001-24
     CN 1025659
                                                       B22C001-24
     CN 1069432 A CN 1991-107467 19910814; CN 1025659 C CN 1991-107467 19910814
ADT
PRAI CN 1991-107467
                      19910814
     ICM B22C001-24
IC
FS
     CPI GMPI
FΑ
     NOAB
     CPI: H08-B; M22-A03
MC
```